

09/29/00
jc917 U.S. PTO

10-02-00

A

TRANSMITTAL OF A PATENT APPLICATION

DOCKET NO. 5055.21

I hereby certify that this transmittal of the below described documents is being deposited with the United States Postal Service in an envelope bearing Express Mail postage and an Express Mail Label, with the below serial number, addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231, on the below date of deposit:

Express Mail Label No:	EL566556225US	Name of Person Making the Deposit:	Gloria Gruetzmacher
Date of Deposit:	9/29/00	Signature of the Person Making the Deposit:	<i>Gloria Gruetzmacher</i>

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

INVENTOR(S): Tod M. Grimm

TITLE: DUAL MANIFOLD MOLD WITH ROTATING CENTER PLATE

The Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

TRANSMITTAL OF A PATENT APPLICATION
(UNDER 37 CFR § 1.53)

Transmitted herewith is the above identified patent application including:

- ☒ Specification, claims and abstract, totaling 23 pages.
- ☒ Formal drawings, totaling 8 pages.
- ☐ Informal drawings, totaling _____ pages.
- ☐ Information Disclosure Statement.
- ☒ Declaration and Power of Attorney.
- ☒ Assignment(s) to Tech Mold, Inc.
- ☒ A verified statement to establish Small Entity Status under 37 CFR 1.9 and 37 CFR 1.27.
- ☐ Other: _____

FEE CALCULATION (for a small entity)

Fee Items	Claims Filed	Included w/basic fee	Extra Claims	Fee Rate	Total
Total Claims	16	+20	-0-	x \$09.	-0-
Independent Claims	1	+3	-0-	x \$39.	-0-
Mult. Dependent Claim Fee (one or more)				x\$130.	
Assignment Recording Fee				\$40	40.
Basic Filing Fee				\$345.	345.
TOTAL FEES					385.

☒ A check in the amount of \$ 385. to cover the filing fee and ☒ assignment is enclosed.

Date: 9/29/00
Law Offices of LaValle D. Ptak
4420 N. Saddlebag Trail, #102
Scottsdale, Arizona 85251
(602) 994-1003

LaValle D. Ptak
LaValle D. Ptak
Registration No. 19,877

STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(c))—SMALL BUSINESS CONCERN

Docket Number (Optional)
5055.21

Applicant, Patentee, or Identifier: Tod M. Grimm

Application or Patent No.: _____

Filed or Issued: _____

Title: Dual Manifold Mold with Rotating Center Plate

I hereby state that I am

- ☐ the owner of the small business concern identified below.
☒ an official of the small business concern empowered to act on behalf of the concern identified below.

NAME OF SMALL BUSINESS CONCERN Tech Mold, Inc.

ADDRESS OF SMALL BUSINESS CONCERN 1735 W. 10th St., Tempe, AZ 85281

I hereby state that the above identified small business concern qualifies as a small business concern as defined in 13 CFR Part 121 for purposes of paying reduced fees to the United States Patent and Trademark Office. Questions related to size standards for a small business concern may be directed to: Small Business Administration, Size Standards Staff, 409 Third Street, SW, Washington, DC 20416.

I hereby state that rights under contract or law have been conveyed to and remain with the small business concern identified above with regard to the invention described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

If the rights held by the above identified small business concern are not exclusive, each individual, concern, or organization having rights in the invention must file separate statements as to their status as small entities, and no rights to the invention are held by any person, other than the inventor, who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person made the invention, or by any concern which would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

- Each person, concern, or organization having any rights in the invention is listed below:
☒ no such person, concern, or organization exists.
☐ each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

NAME OF PERSON SIGNING William Kushmaul

TITLE OF PERSON IF OTHER THAN OWNER President

ADDRESS OF PERSON SIGNING 1735 W. 10th St., Tempe, AZ 85281

SIGNATURE  DATE 9/21/2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Attorney's Docket No. 5055.21

PATENT

Applicant or Patentee: Tod M. Grimm

Application or Patent No.: /

Filed or Issued: DUAL MANIFOLD MOLD WITH ROTATING CENTER PLATE

For:

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY
STATUS (37 CFR 1.9(f) and 1.27(b))—INDEPENDENT INVENTOR**

As a below named inventor, I hereby declare that I qualify as an independent inventor, as defined in 37 CFR 1.9(c), for purposes of paying reduced fees under Sections 41(a) and (b) of Title 35, United States Code, to the Patent and Trademark Office with regard to the invention entitled DUAL MANIFOLD MOLD WITH ROTATING CENTER PLATE described in

- ☒ the specification filed herewith.
- ☐ application no. /, filed .
- ☐ patent no. , issued .

I have not assigned, granted, conveyed or licensed, and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c), if that person had made the invention, or to any concern that would not qualify as a small business concern under 37 CFR 1.9(d), or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☐ no such person, concern, or organization.
- ☒ persons, concerns or organizations listed below *

**NOTE: Separate verified statements are required from each named person, concern or organization having rights to the invention averring to their status as small entities. (37 CFR 1.27)*

FULL NAME Tech Mold, Inc.

ADDRESS 1735 W. 10th St., Tempe, Arizona 85281

☐ INDIVIDUAL ☒ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME

ADDRESS

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

FULL NAME

ADDRESS

☐ INDIVIDUAL ☐ SMALL BUSINESS CONCERN ☐ NONPROFIT ORGANIZATION

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Tod M. Grimm

Name of inventor



Date 9/21/00

Signature of Inventor

Name of inventor

Date _____

Signature of Inventor

Name of inventor

Date _____

Signature of Inventor

006260" 08452960

DUAL MANIFOLD MOLD WITH ROTATING CENTER PLATE

BACKGROUND

Two-component injection molds are widely used to manufacture a variety of products. Typical of such products are screw caps for beverage cartons which have reclosable spouts consisting of a polyethylene boss and a polypropylene screw cap. The boss and cap are manufactured in a two-component, or two-shot, injection molding machine. In the first shot, the polyethylene boss is molded as a pre-form. This pre-form then is transferred to the finish injection station, where the second shot or injection of the polypropylene screw cap is made. The composite spout/screw cap then is ejected from the machine as a finished part.

In the past, the majority of two-component injection molding machines transferred the pre-form from the first to the second station for the over-molding by rotating a complete mold half (a rotary machine plate), or rotating part of the ejector-side mold half (indexing plate). In both cases, the pre-form and the finished part are on one parting line, side-by-side. A significant drawback of such a technique is that a large mold clamping area is required; and consequently, it is necessary to use large injection molding machines. Large machines are more costly than small machines, thereby increasing the cost of the finished product.

Two-component injection molding machines of the type described immediately above, while requiring relatively large machines for effecting the operation, still are reasonably practical for molding

1 relatively small parts, such as beverage carton caps of the type
2 described above. For products which have larger dimensions,
3 however, such as toothbrushes which are several inches long, such
4 conventional two-component injection molds require very large
5 injection molding machines because of the relatively long
6 longitudinal dimensions of the toothbrush handles. Several inches
7 are required for each set (the pre-form side and the second shot
8 side), as opposed to only one or two inches (for each part) for
9 beverage carton caps, or the like.

10 In an effort to reduce the size of the injection molding
11 machine required for two-component molded parts, a mold with a
12 rotating center plate between a fixed plate and a movable plate has
13 been devised. This mold is particularly useful for producing the
14 two-component beverage carton caps described above. When the mold
15 is closed, the center plate is sandwiched or stacked between the
16 other two plates. The pre-forms are formed between one side of the
17 center plate and one of the other, generally conventional plates.
18 The second shot or completion of the product then is formed between
19 the other side of the center plate and the other one of the
20 conventional plates. The mold then is opened; and the two-
21 component finished products are ejected. The center plate is
22 rotated to place the pre-form parts into position for injection of
23 the second mold, and readying the mold for formation of the pre-
24 forms on the side from which the finished products have been
25 ejected. Each cycle of operation effects a 180° rotation of the
26 center plate about its vertical center line (or a center line

perpendicular to the movement of the other two plates toward and away from the center plate). The utilization of the rotating center plate, onto which the other two plates are closed and opened, permits the assembly to be placed in a smaller injection molding machine than would otherwise be required to produce the same number of parts in each cycle from a machine using a rotary machine plate or an indexing plate.

Even though the rotating center plate mold described above is an improvement over conventional two-shot molding machines, it still is impractical for use on elongated objects, such as toothbrushes and the like, for the reasons mentioned above in conjunction with the discussion about such products.

Therefore, it is desirable to provide a two-component injection mold for manufacturing two-component elongated products, which may be used with relatively small injection molding machines, and which employs a floating rotatable center plate mounted in a frame between a pair of reciprocating mold plates in which the rotatable mold plate is used to form only a portion of an elongated product to be produced by the mold.

SUMMARY OF THE INVENTION

It is an object of this invention to provide an improved two-component injection mold.

It is another object of this invention to provide an improved two-component injection mold using a rotating center plate.

It is an additional object of this invention to provide an

1 improved two-component injection mold using a rotating center plate
2 carried by a floating frame.

3 It is a further object of this invention to provide an
4 improved two-component injection mold utilizing three mold plates,
5 the central one of which rotates on an axis perpendicular to the
6 opening and closing direction of movement of the mold plates;
7 wherein the rotating mold plate is mounted in an open frame to
8 permit passage of portions of the other mold plates on either side
9 of the rotating plate.

10 In accordance with a preferred embodiment of this invention,
11 an injection mold for manufacturing two-component elongated members
12 includes first and second mold cavity members mounted for relative
13 movement toward and away from one another in each cycle of
14 operation, to close and open the mold, respectively. A central
15 frame member, designed to overlie at least a portion of each of the
16 first and second mold cavity members when the mold is closed,
17 carries a rotatable mold plate located between a portion of each of
18 the first and second mold cavity members for engagement thereby
19 when the mold is closed. The rotatable mold plate is designed to
20 rotate 180° for each closing and opening cycle of the first and
21 second mold cavity members.

22
23 BRIEF DESCRIPTION OF THE DRAWINGS

24 Figure 1 is a perspective view of an injection molding machine
25 diagrammatically illustrating the location of a preferred
26

embodiment of the invention therein;

Figure 2 is a diagrammatic perspective representation of the preferred embodiment of the invention;

Figures 3A, 3B and 3C are diagrammatic representations of a cycle of operation of the preferred embodiment of the invention;

Figure 4 is a detailed front view of a portion of the preferred embodiment of the invention;

Figure 5 is a partial bottom view of a portion of the embodiment shown in Figure 4;

Figure 6 is a top closed view of the preferred embodiment of the invention;

Figure 7 is a bottom detailed view of a portion of the embodiment shown in Figures 4 and 6;

Figure 8 is a bottom detailed view of another portion of the embodiment of the invention shown in Figures 4, 5 and 6;

Figure 9 is a detail of the central portion of the embodiment shown in Figures 6 and 10; and

Figure 10 is a top view of the preferred embodiment of the invention showing the mold in its open position.

DETAILED DESCRIPTION

Reference now should be made to the drawings, in which the same reference numbers are used throughout the different figures to designate the same components. Figure 1 shows a typical injection molding machine 10, with which the embodiment of this invention may be used. The injection molding machine 10 may be of any standard

1 suitable configuration used for two-component molding of products.
2 Such a machine typically includes a control panel 12 for
3 controlling its operation. In addition, plastic material for
4 injection into the mold cavities and the mold plates is supplied
5 through a pair of injection rams (one for each of the two different
6 components to be molded), one of which 14 is illustrated in Figure
7 1.

8 In Figures 1, 2 and 3, the details of the standard mold
9 blocks, including the manifolds, plastic delivery system, cooling
10 lines and the like, have been removed to show a diagrammatic
11 arrangement of the mold plates or mold cavity plates used in a
12 preferred embodiment of the invention for molding toothbrush
13 bodies. To accomplish this, a fixed mold block 18, carrying mold
14 plates 18A and 18B for two separate manifold systems is provided.
15 The mold plate 18A is injected with the first material for a
16 toothbrush pre-form; whereas the second plate 18B includes a
17 manifold for injection molding the second material to form a two-
18 component toothbrush handle. Figures 4 and 10 illustrate these
19 different plate portions 18A and 18B most clearly; although they
20 are diagrammatically indicated in Figure 3B also.

21 In conjunction with the fixed mold block 18, there is a
22 movable mold block 16, again mounted on conventional apparatus in
23 an injection molding machine for movement toward and away from the
24 mold block 18 to close and open the mold, respectively. The mold
25 which is illustrated is a straight pull mold, which slides on four
26 pairs of guide pins located, respectively, at the two lower corners

1 and two upper corners of the mold assembly. Only one pair of these
2 guide pins, 50 and 52, is illustrated in Figures 7 and 10 for
3 purposes of clarity, since each pair is identical to the pair 50/52
4 which is illustrated. As is most apparent from Figure 4, the guide
5 pins extend through two pairs of lower guide pin holes 34 and two
6 pairs of upper guide pin holes 36 formed through the various
7 components of the mold blocks 16, 18 and a movable frame 30 for a
8 central mold plate.

9 Before entering into a description of the detailed mechanism
10 shown in Figures 4 through 10, a brief description of the overall
11 operation of the preferred embodiment of the invention is
12 considered in order. This description is made in conjunction with
13 Figures 2, 3A, 3B and 3C, which diagrammatically illustrate the
14 basic operating characteristics and general functional features of
15 the preferred embodiment of the invention shown in detail in
16 Figures 4 through 10. As shown in Figures 2 and 3, the mold for
17 making toothbrush handles or other elongated bodies, includes a
18 first mold block 18 having two sides or plates 18A and 18B (Figure
19 3B). Opposing the mold block 18 is a movable mold block 16, which
20 is designed to move horizontally in the mold machine of Figure 1 in
21 the direction of the double arrows, shown in Figure 2 and the
22 arrows shown in Figures 3A and 3C, to open and close the mold
23 cavities formed between the plates 16A and 16B, which correspond
24 and mate with the plates 18A and 18B, respectively. This is most
25 apparent from an examination of Figures 3A to 3C.

26 In between the mold blocks 18 and 16 is a movable frame 30

1 (not shown in Figures 2 and 3), which carries a rotatable plate 20
2 designed for rotation about a vertical axis 24, as illustrated in
3 Figures 2 and 3B. As is apparent from both Figures 2 and 3, the
4 rotatable mold plate 20 has two offset sections "A" and "B", which
5 are designed to fit into corresponding recesses 19 and 17 on the
6 mold blocks 18 and 16, respectively. The portions A and B are
7 identical in external configuration; so that either of them fits
8 into either of the recesses 17 and 19, as most clearly shown in
9 Figures 3A and 3C.

10 In the operation of the mold machine carrying the mold blocks
11 16, 18 and the frame 30 in which the rotatable plate 20 is mounted,
12 the cycle originally commences with the mold closed and the segment
13 A of the rotatable central plate nested into the recess 19 of the
14 mold block 18 and the segment B of the rotatable central plate
15 nested into the recess 17 of the mold block 16. The mold plate 18
16 extends beyond the segment 20A (in Figure 3A) to abut directly
17 against the corresponding mating portions of the mold plate 16A, in
18 the manner of a standard two-plate straight pull mold. Similarly,
19 portions of the mold plate 16B extend beyond the edge of the
20 rotatable center plate 20B to engage the mating front of the mold
21 plate 18B. This closed configuration is not shown in Figure 3A,
22 which illustrates the position of the various components just after
23 the mold commences opening from the closed position described.

24 When the mold is first closed, the first component plastic
25 material is injected into the first component mating cavities in
26 the mold plates 16A and 18A and in mating cavities in the mold

1 plates 16A and 20A (as illustrated in detail in Figure 4 for the
2 surfaces 18A and 20A). This injection of the first component
3 material forms the pre-form 26 of the toothbrush handle and head.
4 The mold then is opened, as illustrated in the initial stages in
5 Figure 3A. As the block 16 moves away from the fixed position
6 block 18, the central floating frame 30 moves at half the rate to
7 half the distance, to place the rotatable center plate 20A/B at a
8 position midway between the two mold blocks 16 and 18 when the mold
9 is fully opened. This is diagrammatically illustrated in Figure
10 3B, and as illustrated in detail in Figure 10.

11 Either upon fully reaching the position shown in Figures 3B
12 and 10, or as the various components move from the closed position
13 to the open position, the central rotatable plate 20 is rotated
14 180° in the direction of the arrows shown in Figures 3B and 10 to
15 reverse the positions of the rotatable plate portions A and B, as
16 shown in Figures 3A and 3B. At this time, the pre-form 26 is
17 rotated to the position on the right; and (in all but the first
18 cycle of operation), the finished two-component toothbrush handle
19 28 is rotated to the left-hand side of the mold, from the right, as
20 illustrated in Figure 3B. As indicated by the arrow attached to
21 the toothbrush handle 28 in Figure 3B, suitable mechanism is used
22 to eject the finished toothbrush handle from this open mold
23 position to prepare the mold for the next cycle of operation.

24 Consequently, when the mold once again closes as shown in
25 Figure 3C, a new pre-form 26 is formed on the left-hand side, while
26 simultaneously, the second shot of plastic is applied through a

1 manifold on the plate 18B to complete the molding of the second
2 component around the pre-form handle 26. The mold then opens; and
3 the cycle described above is repeated, with the simultaneous
4 formation of pre-forms on the left-hand side of the mold plates
5 shown in Figures 3A through 3C and formation of the finished
6 product on the right-hand side of the mold plates, as shown in
7 Figures 3A through 3C. In each cycle of operation, the central
8 rotating plate 20 A/B rotates 180°; and upon completion of the
9 rotation, the finished parts 28 are ejected prior to reclosure of
10 the mold as shown in Figure 3C.

11 It is important to note, even from the diagrammatic
12 representation shown in 3B, that only the head portion (of a
13 toothbrush handle) or a small percentage of the total length of the
14 toothbrush handle body remains in a cavity in the rotatable plate
15 20. In actuality, only the portion of the toothbrush handle which
16 subsequently has bristles inserted into it is the portion which is
17 carried in the mold sections A and B of the rotatable central mold
18 plate 20. The rest of the pre-form, as well as the finished
19 handle, other than the head or bristle portion, extends beyond the
20 central rotating plate 20A/B more than four to six inches across.
21 The toothbrush handles extending substantially 180° outwardly from
22 both sides of the plate 20 A/B may have an overall length of 14 or
23 15 inches. Thus, a relatively small mass for the rotatable plate
24 20 is required, compared to what would be required if the entire
25 pre-form (and, therefore, finished product) needed to be carried in
26 a cavity on the rotatable plate 20.

1 To accomplish the operation which has been outlined above in
2 conjunction with the diagrammatic drawings of Figures 2 and 3, the
3 mold shown in detail in Figures 4 through 10 has been designed. An
4 important component of this mold is the mounting of the rotatable
5 plate 20 in an open rectangular frame 30 (shown most clearly in the
6 end view of Figure 4). The plate 20 is pivotally mounted by means
7 of a central pivot mechanism 24 extending from the top to the
8 bottom of the opening 32 in the frame 30. The distance between the
9 edges of the offset portions A and B of the rotatable plate 20 and
10 the vertical edges or sides of the opening 32 in the frame 30 is
11 selected to be great enough to permit the toothbrush handle
12 extensions for the pre-form 26 and for the finished handles 28 to
13 rotate within the frame 30.

14 The cavities in the mold plates 18A and 18B for the lowermost
15 25% of the plates 18A and 18B are shown through the open frame in
16 Figure 4 (as would be viewed from the movable mold block 16). The
17 upper segments of the plates 18A and 18B are identical to the
18 lowermost segment, but the details are not shown to avoid
19 cluttering of the drawing.

20 It also can be seen from an examination of the cavities shown
21 in the plate surface 20A and 18A, that the pre-form for the entire
22 toothbrush, including the portion in which bristles are
23 subsequently to be formed (in plate 20 of Figure 4), forms a
24 continuous cavity with respect to the mold plate surface 16A. The
25 reverse side of the plate 20, showing the position where the second
26 material is molded onto the pre-form, has no corresponding mold

The offset mold plates 20A and 20B are identical. This is apparent from a consideration of Figures 2 and 3A, and the description provided previously.

As mentioned previously, the sliding mold plate 16 and the central floating frame 30 are moved on pairs of guide pins, such as the guide pins 50 and 52, extending through the guide pin hole sets 34 and 36, shown most clearly in Figure 4. Figure 7 shows the location of the set of guide pins 50 and 52 when the mold is in its closed position; and Figure 10 shows the position of those same guide pins with the mold in its open position.

Portions of the top of the frame 30 and of the mold plates 16 and 18 have been removed to show the parting lines between the various components of the mold in its closed injection molding position. The vertical sides of the frame 30 are shown at each end

1 of the apparatus of Figure 6, where it can be seen that the mold
2 plate surfaces 16A, 18A, 18B and 16B extend through the frame
3 opening 32 beyond the rotatable plate 20A/20B to engage mating
4 cavity sections on one another. Part of the plate 18A also engages
5 the front surface of the facing mold plate 20A in the rotatable
6 mold plate 20. The corresponding face of the face of the mold
7 plate 16B engages the pre-form carried on the mold plate 20B (as
8 illustrated in Figure 6). Obviously for the next subsequent cycle
9 of operation, the positions of the mold plates 20A and 20B will be
10 180° reversed. The plates 20A and 20B are identical, and the
11 operation is identical for each cycle of operation.

12 By utilizing the open floating frame 30 in the manner
13 described, a much simpler, smaller and less complex rotatable mold
14 is possible than would be the case if the entire pre-form and the
15 entire finished product had to be carried in cavities on the
16 central rotating portion. As is readily apparent, especially in
17 Figures 9 and 10, the toothbrush handle, both on the pre-form and
18 on the finished product, extends well beyond the bristle portion,
19 which is the only part carried on the faces 20A and 20B of the
20 central rotatable plate 20.

21 When the mold is in the position shown in Figure 6, injection
22 of the pre-form plastic is supplied through runners 60 of the plate
23 18A to form the pre-form 26 in cavities in the face of the movable
24 mold plate 16A and the face of the rotatable mold plate 20A.
25 Simultaneously, the second plastic component (which may be a
26 different material, or a material of a different color) is injected

1 through runners similar to the runners 16 of the plate 18B to form
2 the finished two-component handle 28. Again, for purposes of
3 clarity, these runners for injecting the second plastic component
4 are not shown in the drawing, since the manner in which this is
5 done is conventional. It also should be noted that the various
6 cooling channels and the apparatus for supplying cooling fluid
7 through the channels is not described, since the techniques for
8 doing this are conventional and do not form a part of this
9 invention.

10 After formation of the pre-form 26 on the left-hand side as
11 shown in Figure 6, and of the finished two-component handle 28 on
12 the right-hand side of Figure 6, the mold is opened to the position
13 shown in Figure 10. Different techniques can be used to ensure
14 that the central floating plate or frame 30 is located exactly in
15 the center between the plates 16 and 18. A technique, however,
16 which is considered quite effective is to use a pair of racks 40
17 and 42 attached to the plates 16 and 18, as shown most clearly in
18 Figure 8, to operate on a gear set 50 placed in a housing 39 on the
19 bottom of the frame 30, as shown in Figures 4, 5, 8 and 10. These
20 racks 40 and 42 rotate a freely pivoted gear 50 mounted on the
21 frame 30 such that for each inch of movement of the plate 16 toward
22 and away from the plate 18, the frame 30 moves in the corresponding
23 direction one-half inch. This type of mechanism is well known, and
24 is suitable for the operation of the mold system of a preferred
25 embodiment of this invention.

26 Ideally, although only one rack and gear set 40, 42, 50 has

1 been illustrated in detail in the drawings, four such rack and gear
2 sets are provided to ensure accurate positioning. The four sets
3 are located at the lower corners and the upper corners of the frame
4 30 and are illustrated in Figure 4, and two of them are illustrated
5 in Figure 5. The rack sets include the set 40/42 just described
6 and a mating set 44/46 located in a housing 49 on the opposite side
7 of the bottom of the center frame member 30. Corresponding sets on
8 the upper ends (or corners, as viewed in Figure 4) of the floating
9 frame 30 include racks 41, 43, and 45, 47. All of these racks
10 operate on gears similar to the gear 50 attached for free rotation
11 on the frame 30. By utilizing four sets of identical racks,
12 twisting or rocking of the frame 30 during the cycle of operation
13 of the machine is reduced to a minimum.

14 Reference now should be made to the enlarged view of Figure 9,
15 which shows the central rotating plate 20 with the two sections 20A
16 and 20B illustrated. When the plate rotates, at the end of a full
17 two-step operating cycle, to present the finished two-component
18 toothbrush handle 28 to the position shown on the left-hand side in
19 Figure 9, a piston 62 is operated to move downwardly (as viewed in
20 Figure 9) to withdraw a plurality of pins 60 (only one of which is
21 shown, to avoid cluttering the drawing) from the bristle holes in
22 the head of the toothbrush handle 28. The pins 60 hold the pre-
23 form 26 in place as the central rotatable plate 20 is rotated 180°
24 in the operation of the machine as described previously.
25 Withdrawal of the pins from the handle 28 by the piston 62 effects
26 release of the handle 28, which then drops from the machine as

1 diagrammatically indicated in Figure 1. The handles 28 then are
2 supplied either to a bin, such as the bin 22 of Figure 1, or to a
3 conveyor for subsequent operation by a bristle inserting machine.
4 Because a relatively large number of pins 60 extend into the pre-
5 form 26 (and also into the finished two-component handle 28), the
6 pre-form 26 is held firmly in place during rotation of the central
7 rotating plate 20; so that alignment of the plastic pre-form 26
8 with corresponding cavities in the faces 18B and 16B of the
9 reciprocating mold plates is ensured for the second shot, as
10 described.

11 The foregoing description of the preferred embodiment of the
12 invention is to be considered as illustrative and not as limiting.
13 Various changes and modifications may be made to perform
14 substantially the same function, in substantially the same way, to
15 achieve substantially the same result by those skilled in the art,
16 without departing from the true scope of the invention as defined
17 in the appended claims.
18
19
20
21
22
23
24
25
26

WHAT IS CLAIMED IS

1
2
3 1. An injection mold for manufacturing two-component
4 elongated members including in combination:

5 first and second mold cavity members mounted for relative
6 movement toward and away from one another in each cycle of
7 operation to close and open the mold, respectively; and

8 a central frame member through which at least a portion
9 of each of the first and second mold cavity members extend to
10 engage one another when the mold is closed, the central frame
11 member carrying a rotatable mold plate located between a portion of
12 each of the first and second mold cavity members for engagement
13 thereby when the mold is closed.

14
15 2. The injection mold according to Claim 1 wherein the
16 rotatable mold plate rotates about an axis perpendicular to the
17 relative direction of movement of the first and second mold cavity
18 members toward and away from one another.

1 3. The injection mold according to Claim 2 wherein the
2 central frame member is an open rectangular frame with a top, a
3 bottom, and first and second sides interconnecting the top and the
4 bottom, wherein the rotatable mold member is rotatably mounted on
5 a central pivot located between the top and bottom of the frame
6 member and further wherein the rotatable mold plate has transverse
7 dimensions across it between the first and second sides of the
8 frame member which are substantially less than the distance across
9 the opening between the first and second sides of the frame member.

10 4. The injection mold according to Claim 3 wherein portions
11 of the first and second mold cavity members extend past the
12 rotatable mold plate to directly engage one another through the
13 opening in the frame member on each side of the rotatable mold
14 plate when the mold is closed.

15 5. The injection mold according to Claim 4 wherein the
16 rotatable mold plate has first and second faces and is rotated 180°
17 in the central frame member each time the first and second mold
18 cavity members are moved away from one another a predetermined
19 maximum distance, whereupon each successive closure of the mold by
20 movement of the first and second cavity members toward one another
21 causes alternate ones of the first and second faces of the
22 rotatable mold plate to engage corresponding portions of the first
23 and second mold cavity members.
24
25
26

1 6. The injection mold according to Claim 5 wherein the
2 elongated members are toothbrushes with a head portion and a handle
3 portion, and wherein a first component of the two-component
4 toothbrush is used to form the head in a cavity in the first mold
5 cavity member and a corresponding cavity in the rotatable mold
6 plate, and to form a first component of the handle in mating
7 cavities between first portions of the first and second mold cavity
8 members extending through the central frame member, whereupon
9 opening of the mold by relative movement of the first and second
10 mold cavity members away from one another causes the central frame
11 member also to be located one-half the distance between the first
12 and second mold cavity members while rotating the rotatable mold
13 plate with the toothbrush head attached thereto 180° prior to the
14 next cycle of closure of the mold.

15
16 7. The injection mold according to Claim 6 wherein the second
17 component of the two-component elongated toothbrush is formed
18 between second portions of the first and second mold cavity and the
19 first component of the handle of the toothbrush carried by the
20 rotatable mold plate in the central frame member.

21
22 8. The injection mold according to Claim 7 further including
23 mechanism for ejecting finished two-component toothbrushes from the
24 rotatable mold plate when the first and second mold cavity members
25 are moved away from one another.
26

1 9. The injection mold according to Claim 1 wherein the
2 elongated members are toothbrushes with a head portion and a handle
3 portion, and wherein a first component of the two-component
4 toothbrush is used to form the head in a cavity in the first mold
5 cavity member and a corresponding cavity in the rotatable mold
6 plate, and to form a first component of the handle in mating
7 cavities between first portions of the first and second mold cavity
8 members extending through the central frame member, whereupon
9 opening of the mold by relative movement of the first and second
10 mold cavity members away from one another causes the central frame
11 member also to be located one-half the distance between the first
12 and second mold cavity members while rotating the rotatable mold
13 plate with the toothbrush head attached thereto 180° prior to the
14 next cycle of closure of the mold.

15
16 10. The injection mold according to Claim 9 wherein the
17 second component of the two-component elongated toothbrush is
18 formed between second portions of the first and second mold cavity
19 and the first component of the handle of the toothbrush carried by
20 the rotatable mold plate in the central frame member.

21
22 11. The injection mold according to Claim 10 further
23 including mechanism for ejecting finished two-component
24 toothbrushes from the rotatable mold plate when the first and
25 second mold cavity members are moved away from one another.
26

12. The injection mold according to Claim 1 wherein the central frame member is an open rectangular frame with a top, a bottom, and first and second sides interconnecting the top and the bottom, wherein the rotatable mold member is rotatably mounted on a central pivot located between the top and bottom of the frame member and further wherein the rotatable mold plate has transverse dimensions across it between the first and second sides of the frame member which are substantially less than the distance across the opening between the first and second sides of the frame member.

13. The injection mold according to Claim 12 wherein portions of the first and second mold cavity members extend past the rotatable mold plate to directly engage one another through the opening in the frame member on each side of the rotatable mold plate when the mold is closed.

14. The injection mold according to Claim 1 wherein the rotatable mold plate has first and second faces and is rotated 180° in the central frame member each time the first and second mold cavity members are moved away from one another a predetermined maximum distance, whereupon each successive closure of the mold by movement of the first and second cavity members toward one another causes alternate ones of the first and second faces of the rotatable mold plate to engage corresponding portions of the first and second mold cavity members.

1 15. The injection mold according to Claim 14 wherein portions
2 of the first and second mold cavity members extend past the
3 rotatable mold plate to directly engage one another through the
4 opening in the frame member on each side of the rotatable mold
5 plate when the mold is closed.

6 16. A method for manufacturing two-component injection molded
7 elongated members including the steps of:

8 mounting first and second mold cavity members in a
9 molding machine for relative movement toward and away from one
10 another in each cycle of operation to close and open a mold,
11 respectively;

12 locating an open frame in the closed position of the mold
13 which surrounds and overlies at least a portion of each of the
14 first and second mold cavity members;

15 placing a rotatable mold plate in the frame for rotation
16 about an axis perpendicular to the direction of relative movement
17 of the first and second mold cavity members toward and away from
18 one another; and

19 rotating the rotatable mold plate 180° each time the
20 first and second mold cavity members are moved away from one
21 another to open the mold to thereupon rotate pre-forms and finished
22 parts made in the mold 180° for each cycle of operation.
23
24
25
26

ABSTRACT

An injection mold for manufacturing two-component elongated members, particularly toothbrushes, includes first and second mold cavity members which are mounted for relative movement toward and away from one another to open and close the mold, respectively. These cavity members are designed to have at least a portion of each of them extend through an open central frame which carries a rotatable central mold plate in it. The central mold plate is configured to engage parts of the first and second mold cavity members, which do not directly engage one another through the opening in the frame. In the operation of the mold, a pre-form is formed on one side, between the first and second mold cavity members extending through the frame, and between one of those mold cavity members and the rotatable mold plate. When the mold then is opened, the rotatable mold plate in the central frame member is rotated 180° to place the pre-form on the opposite side of the mold. The mold then is closed, and the second component is injected in such opposite sides of the mold. After a new injection cycle has been completed, the pre-form is simultaneously formed on the first side of the mold and the finished product is formed on the other. The mold again is opened. The central frame moves one-half the distance between the first and second mold cavity members; and the rotatable mold plate is rotated 180° in each cycle. The finished product is ejected, so that a new pre-form can be molded, as described above.




FIG. 1




FIG. 2







FIG. 4

FIG. 5






FIG. 10

DECLARATION FOR PATENT APPLICATION

DOCKET NUMBER
5055.21

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.
I believe I am the original, first and sole inventor (if only one name is listed below)
or an original, first and joint inventor (if plural names are listed below) of the subject
matter which is claimed and for which a patent is sought on the invention entitled

DUAL MANIFOLD MOLD WITH ROTATING CENTER PLATE, the specification of
which is attached hereto unless the following box is checked:

☐ was filed on _____ as United States Application Number or PCT International
Application Number _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified
specification, including the claims, as amended by any amendment referred to above.
I acknowledge the duty to disclose information which is material to patentability as defined
in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119(a)-(d) of
any foreign application(s) for patent or inventor's certificate listed below and have also
identified below any foreign application for patent or inventor's certificate having a filing
date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Claimed

(Number)

(Country)

(Day/Mo/Year Filed)

☐ Yes ☐ No

(Number)

(Country)

(Day/Mo/Year Filed)

☐ Yes ☐ No

I hereby claim the benefit under Title 35, United States Code, §119(e) of any United States
provisional application(s) listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States
application(s) listed below and, insofar as the subject matter of each of the claims of this
application is not disclosed in the prior United States application, in the manner provided by
the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose
information which is material to patentability as defined in Title 37, Code of Federal
Regulations, §1.56 which became available between the filing date of the prior application
and the national or PCT International filing date of this application.

(Application No.)

(Filing Date)

(Status- patented, pending, abandoned)

(Application No.)

(Filing Date)

(Status- patented, pending, abandoned)

I hereby appoint the following attorney and/or agent to prosecute this application and to
transact all business in the Patent and Trademark Office connected therewith:

LaValle D. Ptak

Registration No. 19,877

Address all telephone calls to: LaValle D. Ptak at (480) 419-9019

Address all correspondence to: LaValle D. Ptak Payor #001321

28435 N. 42nd St., Ste. B


Cave Creek, Arizona 85331

I hereby declare that all statements made herein of my own knowledge are true and that all
statements made on information and belief are believed to be true; and further that these
statements were made with the knowledge that willful false statements and the like so made
are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United
States Code and that such willful false statements may jeopardize the validity of the
application or any patent issued thereon.

Full name of sole or first inventor (given name, family name) Tod M. GrimmInventor's signature [Signature] Date 9/21/00Residence 19440 N. 12th St., Phoenix Citizenship USA

Arizona 85024

United States Patent & Trademark Office
Office of Initial Patent Examination -- Scanning Division



Application deficiencies were found during scanning:

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

☐ Page(s) _____ of _____ were not present
for scanning. (Document title)

There are 7 sheets of drawings.

☐ Scanned copy is best available.